

Name:
Roll No:



UNIVERSITY OF PETROLEUM AND ENERGY STUDIES

End Sem Examination, DEC-2021

Programme Name: B.Tech Applied Petroleum Engineering (Upstream)
Course Name: Mechanics of Drilling Engineering
Course Code: PEAU2006

Semester: III
Time: 03 hrs
Max. Marks: 100

Instructions:

- All questions are compulsory.
- However, internal choice has been provided. You have to attempt only one of the alternatives in all such questions.
- Write the answers on an A4 sheet with your name and roll number mentioned on each page. Write clearly, scan and upload properly.

SECTION A (4x5=20 Marks)
All Questions are compulsory

S. No.		Marks	CO
Q1	Define BOP and its types	04	CO1
Q2	Distinguish between Kick and blow out	04	CO2
Q3	Define Margin of Over pull (MOP) and tripping	04	CO3
Q4	List out components of hoisting system	04	CO1
Q5	Distinguish between SIDPP and SICP	04	CO3

SECTION B (40 Marks)
All the questions are compulsory

Q 6	Explain the procedure of killing a well a) Driller's Method b) Wait and Weight Method	10	CO3
	OR		
Q 6	a) Discuss the functions of any two components used in BHA.		

	b) The weight of drill string in air was calculated to be 400000 lb. While when it is in mud the weight is 320600 lb. Calculate the mud weight in ppg.		
Q 7	Explain the types of drilling fluids. List any five properties of drilling fluids with their significance.	10	CO2
Q 8	Explain the types of drilling bits and also design factors considered while designing a drill bit.	10	CO3
Q 9	Sketch the components of hoisting system on a conventional land drilling rig. OR Sketch the surface facilities of the “Mud circulation system” in a typical land drilling rig.	10	CO1
SECTION-C (40 Marks) All the questions are compulsory			
Q 10	Discuss the Selection criteria parameters of Drill string along with all loads and selection procedure of drill pipe.		
Q 10	OR A drill string consists of 600 ft of 8* in x 2U in drill collars and the rest is a 5 in, 19.5lbm/ft Grade X95 drillpipe. weight of drill collar= 161lbm/ft If the required MOP is 100000 lb and mud weight is 75 pcf(10 ppg), calculate the maximum depth of hole that can be drilled when (a) using new drillpipe and (b) using Class 2 drillpipe having a yield strength (<i>PI</i>) of 394 600 lb.	20	CO4

<p>Q 11</p>	<p>I. Calculate the Drill collar Dimensions and weights:</p> <p>a. What is the weight in air of 200 ft of 9 1/2" x 2 13/16" drill collar?</p> <p>b. What is the weight of this drill collar when immersed in 11 ppg mud?</p> <p>c. It is not uncommon for 5" 19.5 lb/ft drill pipe to be used in the same string as 8 1/4" x 2 13/16" drill collars. Compare the nominal I.D. of this drill pipe and Drill collar size and note the differences in wall thickness of these tubulars.</p> <p>II. The highest rate of penetration for a particular 12 1/4" bit will be achieved when 25,000lbs weight on bit (Wob) is applied to the bit. Assuming that the bit will be run in 12 ppg mud, calculate the length of drill collars required to provide 25,000 lbs Wob.</p> <p>a) Calculate the weight (in air) of 10000 ft of 5" 19.5 lb/ft Grade G drill pipe with 4 1/2" IF connections.</p> <p>b) Calculate the weight of this string in 14 ppg mud.</p> <p>Calculate the length of 9 1/2" x 2 13/16" drill collars that would be required to provide 25,000lbs Wob and keep the drill pipe in tension in 12 ppg mud.</p> <p style="text-align: center;">OR</p>	<p style="text-align: center;">20</p>	<p style="text-align: center;">CO5</p>
<p>Q 11</p>	<p>Discuss the reasons for telescopic wells. Explain the casing types with their functions. List the steps involved in casing design.</p>		

All The Best !!

Tables

CAPACITY AND DISPLACEMENT OF DRILLPIPE

SIZE AND CONN.	NOMINAL WEIGHT LB/FT	GRADE	APPROX WEIGHT LB/FT	CAPACITY		OPEN END DISPLACEMENT		CLOSED END DISPLACEMENT	
				L/M	GALL/FT	L/M	GALL/FT	L/M	GALL/FT
2 ³ / ₈ IF NC26	6.65	E75	7.00	1.68	0.135	1.39	0.107	3.01	0.242
		X95	7.08			1.34	0.108	3.02	0.243
		G105	7.08			1.34	0.108	3.02	0.243
2 ⁷ / ₈ IF NC 31	10.4	E75	10.82	2.36	0.190	2.05	0.165	4.41	0.355
		X95	10.89			2.06	0.166	4.42	0.356
		G105	10.89			2.06	0.166	4.42	0.356
		S135	11.20			2.12	0.171	4.48	0.361
3 ¹ / ₂ IF NC38	9.5	E75	10.39	4.54	0.366	1.97	0.159	6.51	0.525
	13.3	E75	13.86	3.88	0.312	2.63	0.212	6.51	0.524
		X95	14.32	3.96	0.319	2.71	0.218	6.67	0.537
		G105	14.38	3.87	0.312	2.73	0.220	6.60	0.532
	15.5	E75	16.42	3.46	0.279	3.11	0.250	6.57	0.529
		X95	16.54			3.14	0.253	6.60	0.532
G105		16.61	3.15			0.254	6.61	0.533	
5 4 ¹ / ₂ IF NC50	19.5	E75	20.99	9.16	0.738	3.98	0.320	13.14	1.058
		X95	21.09			4.00	0.322	13.16	1.070
		G105	21.50			4.08	0.329	13.24	1.087
		S135	22.09			4.19	0.337	13.35	1.075
	25.6	E75	27.01	8.11	0.653	5.12	0.412	13.23	1.065
25.6	X95	28.30	8.10	0.652	5.36	0.432	13.46	1.084	
	G105	28.11	8.09	0.651	5.33	0.429	13.42	1.080	

DRILL COLLAR WEIGHTS (STEEL) POUNDS PER FOOT

lbs/ft — 2.67 (OD² - ID²)

Collar O.D.	BORE OF COLLAR											
	1- ¹ / ₂	1- ³ / ₄	2	2- ¹ / ₄	2- ¹ / ₂	2- ³ / ₄	3	3- ¹ / ₄	3- ¹ / ₂	3- ³ / ₄	4	
3- ³ / ₈	24.4	22.2										
3- ¹ / ₂	26.7	24.5										
3- ³ / ₄	31.5	29.3										
3- ⁷ / ₈	34.0	31.9	29.4	26.5								
4	36.7	34.5	32.0	29.2								
4- ¹ / ₈	39.4	37.2	34.7	31.9								
4- ¹ / ₄	42.2	40.0	37.5	34.7								
4- ¹ / ₂	48.0	45.8	43.3	40.5								
4- ³ / ₄	54.2	52.0	49.5	46.7	43.5							
5	60.2	58.5	55.9	53.1	49.9							
5- ¹ / ₈	67.5	65.3	62.8	59.9	56.8	53.3						
5- ¹ / ₂	74.7	72.5	69.9	67.2	63.9	60.5	56.7					
5- ³ / ₄	82.1	79.9	77.5	74.6	71.5	67.9	64.1					
6	89.9	87.8	85.3	82.5	79.3	75.8	71.9	67.8	63.3			
6- ¹ / ₈	98.1	95.9	93.5	90.6	87.5	83.9	80.1	75.9	71.5			
6- ¹ / ₂	106.6	104.5	101.9	99.1	95.9	92.5	88.6	84.5	79.9			
6- ³ / ₄	115.5	113.3	110.8	107.9	104.8	101.3	97.5	93.3	88.8			
7	124.6	122.5	119.9	117.1	113.9	110.5	106.6	102.5	97.9	93.1	87.9	
7- ¹ / ₄	134.1	131.9	129.5	126.6	123.5	119.9	116.1	111.9	107.5	102.6	97.5	
7- ¹ / ₂	143.9	141.7	139.3	136.5	133.3	129.8	125.9	121.8	117.3	112.5	107.3	
7- ³ / ₄	154.1	151.9	149.5	146.6	143.5	139.9	136.1	131.9	127.5	122.6	117.5	
8	164.6	162.5	149.9	157.1	153.9	150.5	146.6	142.5	137.9	133.1	127.9	
8- ¹ / ₈	175.4	173.3	170.8	167.9	164.8	161.3	157.5	153.3	148.8	143.9	138.8	
8- ¹ / ₂	186.6	184.4	181.9	179.1	175.9	168.6	172.5	164.5	159.9	155.1	149.9	
8- ³ / ₄	198.1	195.9	193.9	190.6	187.4	183.9	180.1	175.9	171.4	166.6	161.5	
9		207.8	205.3	202.4	199.3	195.8	191.9	187.8	183.3	178.5	173.3	
9- ¹ / ₂		232.4	229.9	227.1	223.9	220.4	216.6	212.4	207.9	203.1	197.9	
10			255.9	253.1	249.9	246.4	242.6	238.4	233.9	229.1	223.9	
10- ¹ / ₂			283.3	280.4	277.3	273.8	269.9	265.8	261.3	256.4	251.3	
11					305.9	302.4	298.6	294.4	289.9	285.1	279.9	

MUD DENSITY, GRADIENT AND BUOYANCY FACTOR

NOTE: Buoyancy factor is for STEEL only

Mud density			Gradient psi/ft	Buoyancy Factor	Mud density			Gradient psi/ft	Buoyancy Factor
kg/m ³	lb/gall	lb/ft ³			kg/m ³	lb/gall	lb/ft ³		
1000	8.34	62.4	.433	.873	1800	15.0	112	.779	.771
1010	8.40	62.8	.436	.872	1820	15.2	114	.790	.768
1030	8.50	64.3	.447	.869	1850	15.4	115	.800	.765
1060	8.80	65.8	.457	.866	1870	15.6	117	.810	.762
1080	9.00	67.3	.468	.862	1890	15.8	118	.821	.759
1100	9.20	68.8	.478	.860	1920	16.0	120	.831	.755
1130	9.40	70.3	.488	.858	1940	16.2	121	.842	.753
1150	9.60	71.8	.499	.853	1970	16.4	123	.852	.749
1154	9.625	72.0	.500	.853	1990	16.6	124	.862	.746
1180	9.80	73.3	.509	.850	2010	16.8	126	.873	.743
1200	10.0	74.8	.519	.847	2040	17.0	127	.883	.740
1220	10.2	76.3	.530	.844	2060	17.2	129	.894	.737
1250	10.4	77.8	.540	.841	2090	17.4	130	.904	.734
1270	10.6	79.3	.551	.838	2110	17.6	132	.914	.731
1290	10.8	80.8	.561	.835	2130	17.8	133	.925	.728
1320	11.0	82.3	.571	.832	2160	18.0	135	.935	.725
1340	11.2	83.8	.582	.829	2180	18.2	136	.945	.722
1370	11.4	85.3	.592	.826	2210	18.4	138	.956	.719
1390	11.6	86.8	.603	.823	2230	18.6	139	.966	.716
1410	11.8	88.3	.613	.820	2250	18.8	141	.977	.713
1440	12.0	89.8	.623	.817	2280	19.0	142	.987	.710
1460	12.2	91.3	.634	.814	2300	19.2	144	.997	.707
1490	12.4	92.8	.644	.810	2330	19.4	145	1.01	.704
1510	12.6	94.3	.655	.808	2350	19.6	147	1.02	.701
1530	12.8	95.8	.665	.804	2370	19.8	148	1.03	.698
1560	13.0	97.3	.675	.801	2400	20.0	150	1.04	.694
1580	13.2	98.7	.686	.798	2420	20.2	151	1.05	.692
1610	13.4	100	.696	.795	2450	20.4	153	1.06	.688
1630	13.6	102	.706	.792	2470	20.6	154	1.07	.685
1650	13.8	103	.717	.789	2490	20.8	156	1.08	.682
1680	14.0	105	.727	.786	2520	21.0	157	1.09	.679
1700	14.2	106	.738	.783	2540	21.2	158	1.10	.675
1730	14.4	108	.748	.780	2570	21.4	160	1.11	.673
1750	14.6	109	.758	.777	2590	21.6	162	1.12	.670
1770	14.8	111	.769	.774	2610	21.8	163	1.13	.667